TANDEMBOX antaro, BLUMOTION

Webcode
ID20044 ◄

Drawer, height M (Space requirement 98.5 mm), load bearing class 30/65 kg

- Drawer for TANDEMBOX antaro
- Integrated BLUMOTION for soft and effortless closing action
- Smooth running action
- Fast, tool-free assembly of front
- Two-dimensional front adjustment

Product overview

Drawer suitable for Blum TANDEMBOX antaro.
Double walled drawer sides in
a) Steel in silk white
b) Steel in white aluminium (RAL9006)
With cover caps for drawer sides. Concealed, guided full extension with low-friction cylindrical nylon roller runners and integrated BLUMOTION.
Cabinet profiles and drawer sides in nominal length and load bearing class
a) 270 mm, 30 kg
b) 350 mm, 30 kg
c) 400 mm, 30 kg
d) 450 mm, 30/65 kg
e) 500 mm, 30/65 kg
f) 550 mm, 30/65 kg
g) 600 mm, 65 kg
h) 650 mm, 65 kg

Dynamic carrying capacity: 100,000 opening and closing cycles with selected nominal length and load bearing class. Can optionally be equipped with electric opening support system. Option of combining with side stabiliser. Fast, tool-free assembly of front. Two-dimensional front adjustment. Appropriate ORGA-LINE inner dividing system available as an option. Optional use with “SPACE STEP” (ID20285).

Equipment options

- ► **ID20144** SERVO-DRIVE for box systems LEGRABOX and TANDEMBOX
- ► **ID20151** ORGA-LINE for drawers

Further information

In the print version of the Blum catalogue or online in the Blum browse catalogue under “Planning”
www.blum.com/catalogue