



AVENTOS HL top

Webcode
ID20342 ◀

for lift ups

- Well-suited to small, one-part fronts
- Ideal for applications in high or wall cabinets with fronts above as well as recessed cabinets
- Easy opening, variable stop and silent and effortless closing thanks to the integrated BLUMOTION dampening
- Harmonious gap design thanks to convenient 3-dimensional front adjustment
- Fast assembly and removal of the front using CLIP technology
- Suitable for combination with SERVO-DRIVE for handle-less fronts

Product overview

Blum AVENTOS HL top for lift ups. Compact lift up fitting with a minimum internal cabinet depth of 264 mm. For wooden fronts, wide and narrow alu frames, mitred and rebated applications, as well as thin fronts measuring 8 mm and above. Symmetrical lift mechanism with spring package. Lift system can be stopped in any position using variable lift mechanism strength adjustment. Convenient lift mechanism adjustment from the front. High stability with wide and large-area fronts via cross stabiliser. Integrated opening and closing dampening. Removable lever arm. Simple, tool-free fast installation of the front using clip-on assembly method. Lift mechanism can be attached to the cabinet side before assembly. No parts projecting beyond the cabinet side. Can be combined with the electrical motion support system SERVO-DRIVE. For cabinet heights of 300 to 580 mm. For cabinet widths up to 1,800 mm. 3-dimensional front adjustment: Height ± 2 mm, Side ± 2 mm, Depth ± 2 mm.

Straightforward, minimalist cover cap made of nylon in

- a) silk white
- b) light grey
- c) dark grey

Optional use with Blum fixing system "EXPANDO T" (ID20279) for thin fronts measuring 8 mm and above.

Equipment options

- ▶ ID20142 SERVO-DRIVE for AVENTOS HL top



Further information

In the print version of the Blum catalogue or online in the Blum browse catalogue under "Planning"
www.blum.com/catalogue